

DVR-A07/DVR-107 GENERAL SPECIFICATIONS

Installation Position Horizontal or Vertical installations

DataBuffer Size 2 Mbytes

Transfer Rate

Data Read DVD Maximum 12X CAV (+R 8X CAV)

(sustained) CD Maximum 40X CAV

(over 16 block transfer)

* data transfer rate may not be output if disc is damaged or dirty

Data Write DVD Maximum 8X (sustained) CD Maximum 24X

Access Time DVD-ROM 140 ms (Random Average) CD-ROM 130 ms

Seek Time DVD-ROM 130 ms (Random Average) CD-ROM 120 ms

HOST Interface Specifications

PIO Mode 4, Multi word DMA Mode 2 16.6 Mbytes/sec

Ultra DMA mode 2 33.3 Mbytes/sec

Media Support

DVD DVD-ROM, DVD-R, DVD-RW, +R, +RW, DVD-RAM

(read when outside of cartridge)

CD CD-ROM, CD-R, CD-RW

Audio Output

Line Out $0.75 \text{ Vrms} \pm 0.1 \text{ Vrms}$ (at 10 k Ω load)

Headphone Out 0.6 Vrms \pm 0.2 Vrms (at 32 Ω load) (optional on front of unit)

Power Supply DC + 12 V, 0.03 A; DC + 5 V, 15 A averages

Maximum power consumption of 25.25W

External Dimensions 5 13/16" (W) x 1 11/16" (H) x 7 13/16" (D) (includes front panel) 148mm (W) x 42.3mm (H) x 198mm (D)

Weight 2.42 lbs (1.1 kg)

Operation

Temperature 41° F to 113° F (+5° C to +45° C)

Humidity Range 5% to 85%

Storage Temperature - 40° F to 140° F (- 40° C to +60° C)

Storage Humidity 5% to 90% (no condensation)

Note: Specifications, due to improvements, subject to modification without notice.